S T E Australia Pty Ltd
ABN 54 087 546 450

PO Box 264
Annandale
NSW 2038

28 Easter St
Leichhardt
NSW 2040

tel 02 9560 6419
fax 02 9560 6429
ste@theatrequip.com.au

"Phoenix" aka "Applause"

rev 0 June 2008

Flame Retarded Curtain Velvet

Specifications:

Composition:	100% Cotton Pile
Flame retardant:	Flacavon R
Width:	120 cm
Weight	370gsm
Pieces:	approx. 55 m
Colours	35 available

Testing:

AS 1530.2-1993 Test for Flammability of Materials

Flammability Index:	6

AS 1530.3-1999 Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release

Ignitability Index:	0
Spread of Flame Index:	0
Heat Evolved Index:	0
Smoke Developed Index:	1

BS5867: part 2 – 1980 : Type B

Handling and Maintenance:

Anticipated fabric life	12 to 15 years (general figure only, environmental factors such as UV light exposure, humidity and traffic may further reduce useful life of fabric).
Flame retardant	Do not wet fabric with water, if wetted in any way, it is essential to retreat the fabric to meet flammability requirements. This may also apply after multiple dry cleaning processes or after a period of use in an area with very high humidity.
Cleaning:	Regular vacuuming recommended. Dry Clean Only – white spirit or perchloroethylene solvent without water (to AS 2001.5.7 - 1986). As required by the Building Code of Australia (BCA) NSW Spec C1.10 6 (b) (ii), the fabric will retained flame retardancy effect after a minimum of 5 commercial dry cleaning operations. It is thus recommended that a log be kept of cleaning.
Spot Cleaning:	white spirit or water-free dry cleaning solvent, as per manufacturer's instructions. Test on a concealed area of fabric before proceeding.

• Stage and Studio Curtains • Blackout • Cycloramas • Wide Canvas, Gauze, Theatre Fabrics • Sandbags •
• Tracking Systems • Rigging • Stage Machinery • Flying Systems • Portable Staging • Projection screens •